


### Self Powered LCD Counter/Timer L3/L4 Series



**L3 7 DIGIT COUNTER  
L4 6 DIGIT HOUR METER**

#### Features

- High reliability
- Low cost and small size
- Low operating current
- Wide operating voltage
- Lithium battery (Non-replaceable)
- Display always on
- 100% sealed (IP68)
- High shock and vibration specs.
- Polarity insensitive L3/L4--A model
- Silent operating, no moving parts
- Wide voltage range covering most AC/DC applications
- Free contact application when power not available
- Solid state electronics
- Quartz Crystal
- Made in the U.S.A.

ENM's Series L3/L4 AC/DC or Free contact is offered as a pulse counter or hour meter. It features an 7 digit LCD display with self-powered CMOS circuit. These units are powered by an internal lithium battery. The totalizing counter or hour meter can be with and without external electronic reset. The total running count or time is displayed at all times. The meter is 100% epoxy encapsulated and protected from shock and vibration to keep out the harshest environments plus provide years of service. This instrument is ideal for any application that requires reliable count or time keeping for service maintenance schedules in a small space.

#### Specifications

Capacity:	99999.9 (Hour Meter displays) 99999.99 (Hours and 1/100) 99999.59 (Hours/Minutes) 999.59.59 (Hours/Minutes/seconds) 9999999 (Counter Display) Automatic recycle to zero.
Character Height:	Large 7-digits 7mm (Counter) Large 6-digits 7mm standard (Hour Meter)
Operating Voltage:	L3/L4--A model 5-250 AC/DC L3/L4--B model (free contact) no input voltage is required
Operating Current:	L3/L4--A model 5V = 0.05mA, 250V = 3mA L3/L4--B Model Free Contact (no current)
Count Speed:	12Hz for L3 standard model higher or lower speed count is available
Operating Temperature:	Standard -30°C to +71°C (-22 F to + 159 F)
Humidity:	95% SAE J1378
Vibration Resistance:	SAE J1378
Accuracy:	Better than +/-0.01% for the L4 model Hour Meter
Protected From:	L3/L4--A model Alternator load dump, inductive switching
Mounting Configuration:	See reverse side for detail

HOUR METER (AC/DC INPUT)	L4XA
HOUR METER (FREE CONTACT)	L4XB
COUNTER (AC/DC INPUT)	L3XA
COUNTER (FREE CONTACT)	L3XB

NOTE: REPLACE "X" IN P/N FOR THE CASE STYLE

© ENM Co.